SDS Revision Date: 07/09/2015

## 1. Identification

1.1. Product identifier

Product IdentityNo-Toil Biodegradable Foam Filter OilAlternate NamesNo-Toil Biodegradable Foam Filter Oil

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended useSee Technical Data Sheet.Application MethodSee Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name No-Toil Industries

1327 Harter Rd.

Yuba City, CA 95993

**Emergency** 

**CHEMTREC (USA)** (800) 424-9300 **24 hour Emergency Telephone No.** (530) 671-4645

**Customer Service: No-Toil Industries** 

# 2. Hazard(s) identification

### 2.1. Classification of the substance or mixture

Flam. Liq. 2;H225 Highly Flammable liquid and vapor. Eye Irrit. 2;H319 Causes serious eye irritation.

STOT SE 3;H336 May cause drowsiness or dizziness.

#### 2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



**Danger** 

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

SDS Revision Date: 07/09/2015

### [Prevention]:

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P235 Keep cool.

P240 Ground / bond container and receiving equipment.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection / face protection.

#### [Response]:

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P337+313 If eye irritation persists: Get medical advice / attention.

P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

#### [Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

#### [Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

# 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Polymerised Fatty Acid CAS Number: Proprietary	50 - 75	Not Classified	[1]
Alcohol CAS Number: Proprietary		Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	[1][2]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

- [1] Substance classified with a health or environmental hazard.
- [2] Substance with a workplace exposure limit.
- [3] PBT-substance or vPvB-substance.

<sup>\*</sup>The full texts of the phrases are shown in Section 16.

SDS Revision Date: 07/09/2015

## 4. First aid measures

#### 4.1. Description of first aid measures

**General** In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

**Inhalation** Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give

artificial respiration. If unconscious place in the recovery position and obtain immediate

medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and

seek medical attention.

**Skin** Remove contaminated clothing. Wash skin thoroughly with soap and water or use a

recognized skin cleanser.

**Ingestion** Seek medical attention. If individual is drowsy or unconscious, do not give anything by

mouth. Place individual on the left side with the head down. If individual is conscious and alert, induce vomiting by giving syrup of ipecac or by gently placing two fingers at the back

of the throat. If possible, do not leave individual unattended.

#### 4.2. Most important symptoms and effects, both acute and delayed

Overview

Eye contact - Exposure can cause eye irritation. Symptoms may include stinging, tearing, redness and swelling.

Skin contact – Exposure may cause mild skin irritation. Prolonged or repeated exposure may dry the skin. Symptoms may include redness, burning, drying and cracking, and skin burns. Pre-existing skin disorders may be aggravated by exposure to this material. Skin absorbtion possible, but harmful effects are not expected from this route of exposure under normal contitions of handling and use.

Inhalation – Exposure to vapor or mist is possible. Short term inhalation toxicity is low. Breathing small amounts during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms of exposure may include:

- Irritation (nose, throat, respiratory tract) pre-existing lung disorders e.g. asthma-like conditions may be aggrivated by exposure to this material.
- Impaired coordination
- Confusion
- Central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness)
- · Low blood pressure
- Coma

Ingestion – Single dose oral toxicity is low, swallowing small amounts during normal handling is not likely to cause harmful effects; swallowing large amounts may be harmful. Symptoms may include:

- Gastrointestinal irritation (nausea, vomiting, diarrhea)
- Impaired coordination
- Central nervous system depression.
- Respiratory depression
- · Low blood pressure
- Effects on heart rate
- · Mild, reversable liver effects
- Pulmonary edema

SDS Revision Date: 07/09/2015

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

**Inhalation** May cause drowsiness or dizziness.

**Eyes** Causes serious eye irritation.

# 5. Fire-fighting measures

#### 5.1. Extinguishing media

Carbon dioxide, dry chemical, alcohol foam

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: May form toxic materials, carbon dioxide and carbon monoxide

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Keep cool.

Ground / bond container and receiving equipment.

Use explosion-proof electrical / ventilating / light / equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust / fume / gas / mist / vapors / spray.

#### 5.3. Advice for fire-fighters

Specific fire fighting procedures: Wear self contained breathing apparatus with a full facepiece operated in the positive pressure demand mode when fighting fires. Water may not be effective for fighting fires, water may be used to keep fire-exposed containers cool until fire is out.

Unusual fire and explosion hazards: Never use welding or cutting torch on or near cases of product because product can ignite explosively.

ERG Guide No. 129

### 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

#### 6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

SDS Revision Date: 07/09/2015

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

#### 6.3. Methods and material for containment and cleaning up

Spill procedures: Absorb liquid with absorbent material.

Large spill: Eliminate all ignition sources. Prevent run-off to sewers, streams and other bodies of water. Follow all local, state and federal regulations.

# 7. Handling and storage

#### 7.1. Precautions for safe handling

See section 2 for further details. - [Prevention]:

#### 7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Incompatible materials: No data available.

Keep away from any form of flame or extreme heat.

See section 2 for further details. - [Storage]:

### 7.3. Specific end use(s)

No data available.

# 8. Exposure controls and personal protection

## 8.1. Control parameters

#### **Exposure**

CAS No.	Ingredient	Source	Value
Proprietary	Alcohol	OSHA	TWA 400 ppm (980 mg/m3)STEL 500 ppm
		ACGIH	TWA: 200 ppm STEL: 400 ppm Revised 2003,
		NIOSH	TWA 400 ppm (980 mg/m3) ST 500 ppm (1225 mg/m3)
		Supplier	No Established Limit
Proprietary	Polymerised Fatty Acid	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

#### Carcinogen Data

CAS No.	Ingredient	Source	Value	
Proprietary	Alcohol	OSHA	SHA Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;	
Proprietary	Polymerised Fatty Acid	OSHA	Select Carcinogen: No	

07/09/2015 **SDS Revision Date:** 

NTP	Known: No; Suspected: No	
IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	

8.2. Exposure controls

Respiratory If workers are exposed to concentrations above the exposure limit they must use the

appropriate, certified respirators.

**Eves** Goggles recommended.

Skin Gloves (vinyl, nitrile, latex, etc.) should be used if there will be direct contact with product **Engineering Controls** 

Provide adequate ventilation to maintain airborne levels below recommended exposure

**Other Work Practices** Use good personal hygiene practices. Wash hands before eating, drinking, smoking or

using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

# 9. Physical and chemical properties

**Appearance** Red Liquid Odor Slight Alcohol **Odor threshold** Not determined Not Measured Hq Melting point / freezing point Not Measured

Initial boiling point and boiling range 180 F/82.22 C (at 760 mmHg)

**Flash Point** 68 F/20 C **Evaporation rate (Ether = 1)** 7.70

Flammability (solid, gas) Not Applicable

Upper/lower flammability or explosive limits Lower Explosive Limit: Not Measured

**Upper Explosive Limit:** Not Measured

Vapor pressure (Pa) 33.00 mmHg **Vapor Density** 2.07 (Air = 1)**Specific Gravity** 0.789 (H2O = 1)Solubility in Water Not Measured Partition coefficient n-octanol/water (Log Kow) Not Measured **Auto-ignition temperature** Not Measured Not Measured **Decomposition temperature** Viscosity (cSt) Not Measured

9.2. Other information

No other relevant information.

## 10. Stability and reactivity

SDS Revision Date: 07/09/2015

#### 10.1. Reactivity

Hazardous Polymerization will not occur.

#### 10.2. Chemical stability

Stable under normal circumstances.

#### 10.3. Possibility of hazardous reactions

No data available.

#### 10.4. Conditions to avoid

Do not use with aluminum equipment at temperatures above 120 F. Avoid contact with strong oxidizing agents, acids, chlorine, acetaldehyde, ethylene oxide, isocyanates.

#### 10.5. Incompatible materials

No data available.

#### 10.6. Hazardous decomposition products

May form toxic materials, carbon dioxide and carbon monoxide

# 11. Toxicological information

#### **Acute toxicity**

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Polymerised Fatty Acid - (Proprietary)	No data available	No data available	No data available	No data available	No data available
Alcohol - (Proprietary)	4,710.00, Rat - Category: 5	12,800.00, Rat - Category: NA	72.60, Rat - Category: NA	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation		Not Applicable

SDS Revision Date: 07/09/2015

Serious eye damage/irritation	2	Causes serious eye irritation.	
Respiratory sensitization		Not Applicable	
Skin sensitization		Not Applicable	
Germ cell mutagenicity		Not Applicable	
Carcinogenicity		Not Applicable	
Reproductive toxicity		Not Applicable	
STOT-single exposure	3	May cause drowsiness or dizziness.	
STOT-single exposure		Not Applicable	
STOT-repeated exposure		Not Applicable	
Aspiration hazard		Not Applicable	

# 12. Ecological information

#### 12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

## **Aquatic Ecotoxicity**

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Polymerised Fatty Acid - (Proprietary)	Not Available	Not Available	Not Available
Alcohol - (Proprietary)	1,400.00, Lepomismacrochirus	100.00, Daphnia magna	100.00 (72 hr), Scenedesmussubspicatus

## 12.2. Persistence and degradability

There is no data available on the preparation itself.

#### 12.3. Bioaccumulative potential

Not Measured

## 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

### 12.6. Other adverse effects

No data available.

# 13. Disposal considerations

#### 13.1. Waste treatment methods

Dispose of in a manner consistent with federal, state and local regulations.

SDS Revision Date: 07/09/2015

# 14. Transport information

IMO / IMDG (Ocean

Isopropanol or Isopropyl

Sub Class: Not Applicable Applicable

**IMDG:** Not Applicable

Transportation)

UN1219

alcohol

Ш

ICAO/IATA

Isopropanol or Isopropyl

UN1219

alcohol

Ш

Air Class: Not

**DOT (Domestic Surface** 

Transportation)

**DOT Hazard Class: 3** 

**14.1. UN number** UN1219

**14.2. UN proper** UN1219, Isopropanol or Isopropyl

alcohol, 3, II

shipping name

14.3. Transport hazard

class(es)

14.4. Packing group

14.5. Environmental hazards

**IMDG** Marine Pollutant: No

14.6. Special precautions for user

No further information

# 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected

regulations are represented.

Toxic Substance

All components of this material are either listed or exempt from listing on the TSCA

Control Act (TSCA) Inventory.

WHMIS Classification B2 D2B

US EPA Tier II Hazards Fire: Yes

Sudden Release of Pressure: No

Reactive: No

Immediate (Acute): Yes Delayed (Chronic): No

## EPCRA 311/312 Chemicals and RQs:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### **EPCRA 302 Extremely Hazardous:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### **EPCRA 313 Toxic Chemicals:**

Alcohol

## Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

## Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### **Proposition 65 - Male Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### New Jersey RTK Substances (>1%):

SDS Revision Date: 07/09/2015

Alcohol

Pennsylvania RTK Substances (>1%):

Alcohol

## 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

**End of Document**